

Model	Line	Standard
VERONA	CRYSTAL	EN ISO 20345:2011
Article	Protection	Availability in stock
86204-00	S2 SRC	AVAILABLE 
	Sole	PU Dual-Density SRC passed



Two-density PU sole, light and flexible. Outsole with transverse design, to improve lengthwise and crosswise grip. SRC Antislip Standard. "Crystal" outsole for maximum grip and no-marking.

Removable insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.

Type	Ankle boot
Upper	Microfiber
Lining	DUALMICRO
Anti-slip Lining	
Removable insole	Flyfit
Sole	PU Dual-Density SRC passed
Toe cap	C.T.C. - Composite Toe Cap
Antiperforation	
Size	35-39 40-48 Weight gr. 470

Working environment

Food and Chemical industry, Components and Automotive

SRC

SRC (SRA+SRB)

		Sole 86 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.40
	HEEL (width ≥ 0.28)	0.32
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (width ≥ 0.13)	0.24

EN ISO 20345:2011

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

