

Model	Line
BIELLA	CRYSTAL
Article	Protection
86205-00	S2 SRC
Sole	

Standard
EN ISO 20345:2011
Availability in stock
AVAILABLE 



PU Dual-Density SRC passed
Two-density PU sole, light and flexible. Outsole with transverse design, to improve lengthwise and crosswise grip. SRC Antislip Standard. "Crystal" outsole for maximum grip and no-marking.

Removable insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection elements




Working environment

Food and Chemical industry, Components and Automotive

SRC

SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.40
	HEEL (SHOULDER-TOE) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (SHOULDER-TOE) ≥ 0.13	

Sole 86 PU - PU
EN ISO 20345:2011

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Type	Low Shoe
Upper	Microfiber Coagulated PU
Lining	Bacteriostatic Teklife 3D
Anti-slip Lining	DUALMICRO
Removable insole	Flyfit
Sole	PU Dual-Density SRC passed
Toe cap	C.T.C. - Composite Toe Cap
Antiperforation	
Size	35-48
Weight gr.	450

Features



Antistatic

EN ISO 20345:2011 6.2.2.2.

0,1 < MΩ < 1000

ANTI-STATIC SHOE

Symbols

