


Model	Line	Standard
PADOVA	CRYSTAL	EN ISO 20345:2011
Article	Protection	Availability in stock
86207-00	SB A E SRC	<b>AVAILABLE</b> 
	Sole	PU Dual-Density SRC passed



Two-density PU sole, light and flexible. Outsole with transverse design, to improve lengthwise and crosswise grip. SRC Antislip Standard. "Crystal" outsole for maximum grip and no-marking.

Removable insole



The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.

Protection elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.

Type	Clogs
Upper	Microfiber
Lining	3D Air circulation 320 gr.
Anti-slip Lining	DUALMICRO
Removable insole	Blowfit
Sole	PU Dual-Density SRC passed
Toe cap	C.T.C. - Composite Toe Cap
Antiperforation	
Size	35-48
Weight gr.	440

Working environment

Food and Chemical industry, Components and Automotive, Finishing-off building

SRC

SRC (SRA+SRB)

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.40
	HEEL RESISTANCE ≥ 0.28	0.32
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL RESISTANCE ≥ 0.13	0.24

Sole 86 PU - PU

EN ISO 20345:2011

Plus



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Features



Antistatic

EN ISO 20345:2011 6.2.2.2.  
0,1 < MΩ < 1000  
ANTISTATISCHER SCHUH

Plus

Symbols

